NHG60M

stone material

automobile

electronic

printing

NHG60M Small Aperture Gloss Meter SCM TÜV CE ISO9001 RoHS FC

Touch screen operation , gloss measurement with one-touch to complete , gloss measurement amazingly simple !

leather

ceramic

DAGHIGHPARTO.COM

دقیق پرتو
DAGHIGH PARTO

شرکت دقیق پرتو
تامین کننده تجهیزات آزمایشگاهی و کنترل کیفی
۰۲۱-۶۶۹۳۷۲۱۴

The new generation of intelligent gloss instrument is more perfect than portable gloss meter , perfect combination of the human body mechanics structural design ,large color touch screen ,one-touch operation and navigational context menu in full screen,gloss measurement amazingly simple.more accurate result .

PRODUCT FEATURES

1.Small aperture: 1.5*2mm
2.60° angle for semi gloss
3.Display 5 sets of measurement data, good for comparison
4.Measuring mode: basic measurement, statistical measurement, continuous measurement, QC measurement (only for GQC6 software)
5.Continuous mode to check uniformity over large areas
6.Connect to PC, more extend functions
7.Input gloss value manually
8.Large touch screen operation, easy to use
9.Beauty appearance, good man-machine communication interface
10.Powerful functions to meet many different requirements
11.Large storage to save over 5000 data
12.Built-in lithium ion rechargeable battery

SPECIFICATION FEATURES

Measure Angle:60°
Comply with standard :ISO 2813、GB/T 9754、ASTM D 523、ASTM D 2457
Measuring Area (mm):1.5*2
Measurement Range:0~1000GU
Division Value:0.1GU
Measurement Range:0-10GU 10-100GU 100-1000GU
Repeatability:± 0.1GU ± 0.2GU ± 0.2%GU
Reproducibility:± 0.2GU ± 0.5GU ± 0.5%GU
Measurement Standard:Conform with JJG696 first class gloss meter working requirement
Chromaticity Corresponding:Corresponding with CIE 1931(2°) under CIE C light source
Errors:±1.5 , ± 1.5%
Measuring Time:0.5s
Dimension:L*W*H : 160mm*75mm*90mm
Weight:350g
Language:Chinese/English
Battery:3200mAh Li-ion Battery, >10000 times(within 8 hours)
Viewing Screen:TFT 3.5 inch, capacitive touch screen
Interface:USB/RS-232
Data Save:Basic mode: 1000, Statistical Mode: 5000, Continuous mode : 5000
Software:GQC6 Quality Control Software with QC report printing functions and more extended functions.
Operation Temperature:0~40° C(32~104°F)
Storage Temperature:-20~50° C(-4~122°F)
Humidity:<85% relative humidity, no condensation
Standard Accessories:Power Adapter, USB cable, User Manual, CD (Including QC software), Calibration Plate
Optional Accessories:Miniature Printer

DAGHIGHPARTO.COM
دقیق پرتو
DAGHIGH PARTO
شرکت دقیق پرتو
تامین کننده تجهیزات آزمایشگاهی و کنترل کیفی
۰۲۱-۶۶۹۳۷۲۱۴