JJ-TEST

Universal Testing Machine

Chengde Jinjian Testing Instrument Co.,Ltd.

DAGHIGHPARTO.COM

دقیق پرتو
DAGHIGH PARTO
شرکت دقیق پرتو
تامین کننده تجهیزات آزمایشگاهی و کنترل کیفی
۰۲۱-۶۶۹۳۷۲۱۴

JJ-TEST

Universal Testing Machine

Universal Testing Machine is suitable for quality control of various fields, including metal wire, nylon wire, plastic, rubber, textile and clothes, packaging etc, for tension, compression and bending, peer and tear test.

STANDARDS

ISO 527, ASTM D 638 and the equivalent.

CHARACTERS

1.The high stiffness frame incorporates a crosshead guidance system to prevent side loading of the test sample.
2.Automatic identification of load cells.
3.Load accuracy of ±0.02% of load cell value provides high dynamic range, thereby reducing the number of load cells required to cover the full force range.
4.Extensometer, inner diameter measurement system and ring stiffness software are available as options.
5.Incorporating world proven 32-bit technology for highly accurate load measurement and rapid data acquisition.
6.XWW series have been authorized CE certificate.
7.Pass CNAS T0544,CNAS T0646 tensile tests.

PARAMETERS

Model	Max. Force	Speed	Tensile space	Crossbeam resolution	Display & Output
XWW-10A	10kN	(0.05-500)mm/min	(0-900)mm	0.001mm	PC control,Printer
XWW-20A	20kN	(0.05-500)mm/min	(0-900)mm	0.001mm	PC control,Printer
XWW-30A	30kN	(0.05-500)mm/min	(0-900)mm	0.001mm	PC control,Printer
XWW-50A	50kN	(0.05-500)mm/min	(0-900)mm	0.001mm	PC control,Printer
UTM-2360	100kN	(0.05-500)mm/min	(0-500)mm	0.001mm	PC control,Printer

SOFTWARE

1.Test automation and batch testing.
2.The stand alone system is capable of storing up to 600 test results.
3.Extensive built-in library of test methods covering ASTM, ISO, DIN, EN and other standards.
4.User configurable test enables users to quickly build advanced multi-stage test routines using simple built-in commands.

DAGHIGHPARTO.COM

دقیق پرتو
DAGHIGH PARTO
شرکت دقیق پرتو
تامین کننده تجهیزات آزمایشگاهی و کنترل کیفی
۰۲۱-۶۶۹۳۷۲۱۴

JJ-TEST

High & Low Temperature Universal Testing Machine

Environmental system enables the testing of material and components under a variety of real world conditions. Cooperating with environmental chamber, XWW series machines can realize variety of tests at low or high temperature.

STANDARDS

ISO 527, ASTM D 638 and the equivalent.

CHARACTERS

1.It consists of three parts: main frame,grips and moveable high & low temperature cabinet.

2.Import full-digital AC servo system and high rigid structure enable high precision of the measuring result. The cabinet, with a double-heat insulation glass door, is convenient to observe the test; stainless steel test cabinet is resistant to corrosive.

3.It is nice in appearance, high in precision and easy to operate, also different kinds of grips shall be provided according to your requirement.

4.This kind of tester has been authorized CE certificate.

PARAMETERS

Accuracy Grade	0.5
Max. Load	20KN
Display resolution	0.001KN
Temperature range	(-70～200)℃（Nytrogen）/(-20～200)℃（Compressor）
Temperature fluctuate	±1℃(high temp.); ±2℃(low temp.)
Distortion tolerance	±0.001mm
Display error	±0.5%
Test speed	(0.05～500)mm/min
Accuracy of speed	±0.5%
Electrical requirement	220V/50Hz, 110V/60Hz (Please specify)
Display method	PC

DAGHIGHPARTO.COM

دقیق پرتو
DAGHIGH PARTO
شرکت دقیق پرتو
تامین کننده تجهیزات آزمایشگاهی و کنترل کیفی
۰۲۱-۶۶۹۳۷۲۱۴

JJ-TEST

UTM Grips

Dumbbell Specimen Maker

This maker is used to make dumbbell, strip as well as other kinds of shape specimen with reference to different standards.

CHARACTERS

Depth of specimen	≤70mm
Width and length of specimen	customization
Power supply	500VA 380VAC 50HZ
Dimension (H×W×H)	(400×400×440)mm

DAGHIGHPARTO.COM

دقیق پرتو
DAGHIGH PARTO
شرکت دقیق پرتو
تامین کننده تجهیزات آزمایشگاهی و کنترل کیفی
۰۲۱-۶۶۹۳۷۲۱۴