YL-S70 Computer-control material testing machine

Introduction

This tester is designed for conduct tensile, compression, bending, shearing, bonding strength, peeling, tearing and other tests for rubber, plastic, leather, metal, nylon line, fabric, paper, aviation, packaging, construction, petrifaction, electrician, vehicle and other materials. It is a basic equipment of quality control, receiving inspection, physical test, mechanics research, material development.







شرکت دقیق پرتو تامین کننده تجهیز ات آرمایشگاهی و کنترل کیفی ۶۶۹۳۷۲۱۴ ه ۲۰

Software display

Single test curve



Multiple test curve





Specification

Capacity	10N, 20N, 50N, 100N, 200N, 500N, 1KN, 2KN, 5KN (can select double capacities preparation)
Display	Computer display mode
Force Resolution	1/500,000
Force Accuracy	≤±0.1%
Stroke Resolution	1/500,000
Stroke Accuracy	≤±0.1%
Test Stroke	450 mm(Customizable)
Test Width	Ø140 mm
Test Speed	0.01~500 mm/min(Customizable)
Acquisition Rate	2000 times / S
Force Switch	N、kN、gf、kgf、lbf、kP、tf(SI)、tf(long)
length Unit	mm、cm、lnch、m、km、um
Stress Unit	Pa、Kpa、Mpa、Gpa、KN/m²、N/m²
Stop Mode	Overload stop, emergency stop button, specimen damage automatic stop, upper & lower limit set automatic stop, automatic reset function
Machine Dimension	62*26*105cm (W×D×H)
Machine Drive	Servo motor drive
Power	400W
Machine Weight	Approx 66kg
Power Supply	220V 50/60HZ 10A
Standard Device	1 set of grips, computer software, USB computer
Optional	Personal computer, grips

Machine structure

AC servo motor drive, precision ball screw drive;

Screw shield using aluminum extrusion, surface blasting, anode satin handle, exquisite; Shell selection of advanced electrostatic spray treatment, durable;

Vertical stroke trim switch;

Quick release connectors, you can easily switch to a different function fixtures; Machine protection: over-travel, over capacity protection, emergency brake switch;

Machine function

دقيق پرتو даднідн ракто	شرکت دقیق پرتو تامین کننده تجهیزات آزمایشگاهی و کنترل کیفی
DAGINGH PARTO	• ¥ 1 - 9 9 9 W Y 1 F

1. Powerful data analysis and statistical curves graphical analysis aids, with zoom, pan, crosshairs, and take other functions.

2. Several historical test data can be transferred to the graphics displayed simultaneously comparative analysis done.

3. Up to 7 interval setting, 40 manual taking points, 120 automatic pick point function. With the maximum, minimum, average, to the level of the average, median, standard deviation, population standard deviation, CPK values and other statistics.

4. Test curve shows: during the test in real time and can be a show of force at the same time - displacement, force - time, displacement - time, stress - strain curve, can easily switch to the screen to see the curve;

5. Custom test methods: with the speed, position shift, given the strength, will power rates, given stress, stress rate constant, constant strain, strain rate and other fixed control mode, enabling complex multi-step control can be nested loop. set automatic return, automatic judgment fracture, auto-zero function.

6. Positive and negative force sensor can be switched;

Packing

Packaged weight: 88KG; Packaged dimensions: 55 × 53 × 123cm (W*D*H) Packaged Volume: 0.358 m³; Packing: protective film, plywood standard export wooden box HS Code:

Optional clamps(for reference)



YG-T003A plane cloth clamp



YG-T003D plane clamp



YG-C003 film puncture



YG-C005 bottle compression fixture



YG-C003A puncture clamp Yuellan 🚔 🜿 🖺 👁



YG-T005 beak clip



YG-T007 eccentric clamp



YG-T006 webbing clamp



YG-T104 tack ring fixture



YG-T001 flat clip




YG-D007 line fixture



YG-C004C compression plate



CE Certificate





شرکت دقیق پر تو تامین کننده تجهیز ات آزمایشگاهی و کنترل کیفی ۶۶۹۳۷۲۱۴ م