



SMV-402 Digital Micro Vickers Hardness Tester

Feature:

SMV-402 Digital Micro Vickers hardness tester is a high-tech and new product combining the optics, mechanic and electrics features. With a novel and pleasing appearance, the internal structure is mainly made by stainless steel parts, has better performance. It can directly shows the test mode, test force, indentation length, dwell time, test numbers, conversion scale, date and time on the large screen. As long as press the eyepiece button after measuring the indentation length, it can automatically get the hardness value and shows on the screen. With the up and down limit alarm function, test results can be saved for checking or be printed out by the built-in printer, and with RS232 interface for connecting to the computer. It can use optional Knoop indenter to measure Knoop hardness. And it can be equipped with LCD video measuring device and CCD image automatic measuring system.

Standard: ISO 6507,ASTM E384,JIS Z2244,GB/T 4340.2

Application:

Suitable for ferrous metal, non-ferrous metals, IC thin sections, coatings, ply-metals; glass, ceramics, agate, precious stones, thin plastic sections etc.; hardness testing such as that on the depth and the trapezium of the carbonized layers and quench hardened layers.



Technical Specification:

Technical Specification	n:					
Model		SMV-402				
Tost Force	gf	10gf, 25gf, 50gf, 100gf, 200gf, 300gf, 500gf, 1000gf				
Test Force	N	0.098N, 0.246N, 0.49N, 0.98N, 1.96N, 2.94N, 4.90N, 9.80N				
test range		1HV~2967HV				
test mode		HV/HK				
loading method		automatic (loading/dwell/unloading)				
shifting objective and indenter		automatic shifting				
conversion scale		HV, HK, HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRK, HR15N, HR30N, HR45N, HR15T, HR30T, HR45T, HS, HBW				
data output		built-in printer, RS232 interface				
hardness reading		LCD display, data can be saved				
total magnification		objective $10 \times (\text{observe})$, $40 \times (\text{measure})$, eyepiece $10 \times$, total: $100 \times$, $400 \times$				
resolution		0.015μm				
dwell time		0~95s				
light source		halogen lamp				
X-Y test table		size: 100×100mm; Travel: 25×25mm; resolution: 0.01mm				
max. height of specimen		90mm				
throat		120mm				
power supply		AC220V, 50Hz				
dimension(LWH)		machine: 495×305×550mm, packing : 600×360×800mm				
weight		Net Weight: 35kg, Gross Weight: 44kg				

Standard accessories:

No.	Name	Qty	No.	Name	Qty
1	instrument main body		12	10× digital measuring eyepiece	1
2	diamond micro vickers indenter	1	13	10×, 40× objective	2
3	weights		14	power cable	1
4	cross test table	1	15	flat clamping test table	1
5	thin specimen test table		16	filament clamping test table	1
6	horizontal regulating screw	4	17	level	1
7	fuse 1A	2	18	halogen lamp 12V, 15~20W	1
8	inner hexagon spanner	1	19	screw driver	1
9	plastic absorbing plate		20	color filter	1
10	0 hardness block 400~500 HV0.2		21	hardness block 700~800 HV1	1
		1	22	manual	1

