

Introduction

ZB-NPY5600 Bursting apparatus is a new machine developed by our company. High precision instrument sensors make it has high precision. With data processing, the data can be directly obtained results, and can automatically reset. It has the advantage of easy operation, easy adjustment, stable performance, can be used in paper, cardboard, rubber, plastic, silk, cotton cloth of non-paper-made materials .

Standards

ISO 2759 GB/T 1539

Main Features

1. Clamping system is pneumatic
2. Operating system real-time display samples bursting strength.
3. Automatic measurements, statistics, print the test results, and has data storage function
4. Micro-printer, high print speed, easy to use, low failure;
5. Mechanical and electrical integration of modern design, compact structure, excellent appearance, easy maintenance
6. Touch screen, Easy to operate

Main technical parameters

Item	ZB-NPY5600
Power	AC220V \pm 10% 50HZ
Measuring range(kPa)	200-5600
Accuracy	\pm 0.5%F. S
Compression speed (ml/min)	170 \pm 15
Clamp pressure(kPa)	\geq 700
Inner dia(mm)	31.5 \pm 0.05
Optional configuration	Air Compressor
Film resistance(kPa)	when the bulge height is 10mm, the pressure is 170~220kpa, when the bulge height is 18mm, the pressure is 250~350kpa

Size and Weight

Dimension	480*420*600mm
Weight	65kg

